

TABLE OF CONTENTS

List of major designations and abbreviations	9
Preface.....	11
Introduction.....	15
1. Thermal spraying of layers and coatings	17
1.1. Methods of depositing layers and coatings	18
1.2. Arc spraying.....	20
1.3. Plasma spraying.....	23
1.4. Flame spraying	26
1.4.1. Flame spraying at subsonic velocities	26
1.4.2. Flame spraying at supersonic velocities	28
1.5. Laser spraying	36
1.6. Cold spraying	39
1.7. Laser alloying and remelting.....	42
1.7.1. Laser alloying	42
1.7.2. Laser remelting of coatings	43
1.8. Comparison of thermal spraying methods	44
2. Selected properties of sprayed coatings.....	49
2.1. Coating formation process	49
2.2. Coating adhesion	51
2.2.1. Effect of surface preparation	52
2.2.2. Effect of temperature.....	52
2.2.3. Effect of kinetic energy	53
2.2.4. Effect of the physical and chemical properties of materials.....	54
2.3. Residual stresses in surface layers	55
2.4. Residual stresses due to thermal mismatch	60
3. Feedstock materials for spraying	64
4. Testing of thermally deposited coatings by flame and detonation methods	69
4.1. Preliminary testing of sprayed coatings by flame and detonation methods	71
4.2. Characterization of feedstock materials	71
4.3. Stresses in the coating–substrate system.....	73
4.4. Construction of an instrument for testing the deflection of a coated substrate after the spraying process	75

4.5. Spraying titanium coatings on ceramic substrates.....	76
4.6. Determination of residual stresses in sprayed coatings	77
4.6.1. Titanium coatings	77
4.6.2. Ti+Al ₂ O ₃ composite coatings	79
4.7. Numerical analysis of residual stresses in titanium and composite coatings	80
4.8. Temperature field during cooling of the coating–substrate system	85
4.8.1. Object of study.....	86
4.8.2. Assumptions for numerical calculations.....	87
4.8.3. Calculation results	88
4.8.4. Comparative analysis of temperature distribution calculation results	93
4.9. Stress investigation in Ti and Ti+Al ₂ O ₃ coatings sprayed on Al ₂ O ₃ substrate by detonation gun method (D-gun).....	99
4.9.1. Feedstock materials	99
4.9.2. Detonation spraying parameters	100
4.9.3. Measurements of deflection in specimens after detonation spraying	101
4.9.4. Stresses in the sprayed coating based on the curvature of the specimen.....	102
4.10. Conclusions.....	106
5. Residual stress modelling in the thermal spraying process	109
5.1. Introduction – physical modelling of the process and generation of residual stresses ...	109
5.2. Methodology adopted for modelling residual stresses in thermally sprayed coatings....	112
5.3. Particle impact modelling using ANSYS-AUTODYN	115
5.4. Modelling of particle impact on the substrate.....	119
5.5. Impact of Ti particles on the Al ₂ O ₃ substrate and particles on the sublayer by detonation spraying.....	120
5.6. Thermo-mechanical model of the thermal spraying process	126
5.6.1. Temperature distributions in the Ti–Al ₂ O ₃ coating–substrate system, detonation spraying	131
5.6.2. Stress distributions in the Ti–Al ₂ O ₃ coating–substrate system, detonation spraying	133
5.6.3. The influence of the substrate preheating temperature on the stresses in the Ti–Al ₂ O ₃ coating–substrate system	136
5.7. The effect of the impact velocity on the residual stresses in the Ti–Al ₂ O ₃ coating–substrate system	145
5.7.1. Results of dynamic calculations for the impact of a feedstock material particle on a ceramic substrate.....	147
5.7.2. Impact of Ti coating particles against the Ti coating sublayer	152
5.7.3. Results of temperature distribution calculations for different particle impact velocities.....	156
5.7.4. Results of specimen deflection and stress distribution calculations for different particle impact velocities	159
5.7.5. Summary of particle spray velocity effects	163
5.8. Conclusions	164
6. Modelling the impact of a single particle on the substrate	166
6.1. Model description.....	166
6.2. Assumptions for the Ti particle model on ceramic and metal substrates	173
6.2.1. Model of spraying Ti particles on Al ₂ O ₃ ceramic substrate ($V = 500$ m/s)	174
6.2.2. Model of spraying Ti particles on Al ₂ O ₃ ceramic substrate ($V = 800$ m/s)	180

6.3. Comparative analysis of particle impact simulations of ceramic and metallic substrates	186
6.3.1. Titanium particle.....	186
6.3.2. Copper particle	192
6.3.3. Particle geometry after impact.....	199
6.4. Modelling of the impact of a heated Ti particle on a ceramic substrate.....	199
6.4.1. Geometric model	199
6.4.2. Model deformation simulation results.....	202
6.4.3. Temperature distribution in the Ti particle–Al ₂ O ₃ substrate system	206
6.4.4. Distribution of reduced stresses in the Ti particle–Al ₂ O ₃ substrate system.....	207
6.5. Conclusions	211
7. Coating testing and modelling of residual stresses in the thermal spraying process using the HVOF method.....	214
7.1. Testing of metal coatings sprayed on Al ₂ O ₃ ceramic substrate.....	214
7.2. Test object	214
7.3. Spraying station.....	215
7.4. Structural studies	219
7.5. Coating wettability tests.....	224
7.5.1. Wettability tests in argon	226
7.5.2. Wettability tests in vacuum.....	227
7.5.3. Conclusions	228
7.6. Residual stress tests in the coating–substrate system.....	228
7.6.1. Determination of residual stresses based on the curvature of the specimen	229
7.6.2. Research on residual stresses in coatings using the X-ray method	231
7.7. Conclusions	234
7.8. Numerical and experimental analysis of residual stresses generated in metallic coatings deposited by HVOF on an Al ₂ O ₃ substrate	235
7.8.1. Impact of Ti particles on the Al ₂ O ₃ substrate.....	235
7.8.2. Temperature distributions in the Ti, Cu, Ni coating system	239
7.8.3. Stress distributions in the Ti (Cu, Ni) coating–Al ₂ O ₃ substrate system	241
7.8.4. Conclusions	245
8. Investigation of strains and stresses in sprayed Ti and Cu coatings using grating interferometry	247
8.1. Grating interferometry method.....	247
8.2. Specimen grating technology	249
8.3. Automatic analysis of fringe images.....	250
8.4. Measuring station	251
8.5. Measurement procedure	253
8.6. Measurements on a titanium coating sprayed on an Al ₂ O ₃ substrate	254
8.6.1. Measurement of displacements in the measuring field of 14.3×14.3 mm prior to cutting	255
8.6.2. Measurement of displacements in the measuring field of 14.3×14.3 mm after cutting	256
8.6.3. Measurement of displacements in the measuring field of 14.3×14.3 mm after the second cutting	259
8.6.4. Measurements in a small measuring field (3.7×3.7 mm)	262

8.7. Measurements on a copper coating sprayed on an Al_2O_3 substrate	264
8.7.1. Measurement of displacements in the measuring field of 14.3×14.3 mm prior to cutting	264
8.7.2. Measurement of displacements in the measuring field of 14.3×14.3 mm after cutting	265
8.7.3. Measurements in a small measuring field (3.7×3.7 mm) after the second cutting	268
8.8. Strain comparison for Cu and Ti coated specimens	270
8.9. Modelling of deflection and residual stresses in Cu/ Al_2O_3 and Ti/ Al_2O_3 systems before and after cutting the plate	273
8.9.1. Cu- Al_2O_3 coating-substrate model	274
8.9.2. Ti- Al_2O_3 coating-substrate model	276
8.10. Comparison of determined residual stresses	279
8.11. Conclusion	279
9. Summary and conclusions	282
Bibliography	291